

# ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215

(414) 344-4500 • FAX (414) 344-4504

WWW.ASAFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

## ATRAACE

# AO-5000<sub>Max.</sub>



Designed to use **Jetbroach Carbide Tipped Annular Cutters**



### Features

- Large 2" x 2" hole drilling capacity
- Uses **Jetbroach** carbide tipped annular cutters
- Durable 48 lb. design
- Powerful two speed motor with 500/750 rpm gear box
- Sealed arbor with through spindle coolant
- Self contained coolant reservoir
- One-Touch arbor system "No tools required for cutter installation and removal"
- Built-in circuit prevents accidental restart
- Precision machined die cast aluminum mainframe, motor, motor slide and arbor support bracket
- One year limited warranty

**Large, deep hole cutting,  
1 1/16"-2" diameter in max. 2" thick plate!  
Extra hole-cutting power!**

#### Standard Accessories

- Pilot pin #UEA0635-O
- Pilot pin #UEA0650-O
- 2.5 mm Allen wrench
- 4 mm Allen wrench
- Safety chain
- 5 mm Allen wrench
- 7 x 8 mm combination wrench
- Sample cutting fluid
- Tool box

#### Specifications

Model	AO-5000		
Power Source (Single Phase)	115 V AC 50 / 60 Hz		
Electric Drill	Rated Power Consumption W	730	
	Rated Current A	7.0	
	No load Speed min <sup>1</sup> /rpm	500 / 800	
Magnet Power Consumption W	75		
Hole-cutting capacity	Cutter	Hole Diameter	Plate Thickness
One-touch type Jetbroach 2" D.O.C.		1 1/8" to 2"	3/8" to 2"
One-touch type Jetbroach 1-3/8" D.O.C.		1 1/16" to 1-9/16"	3/8" to 1-3/8"
Magnet Holding Power	lbs (kgf)	2,200 (1,000)	
Magnet Dimensions	inch (mm)	3-15/16" x 7-15/16" (100 x 200)	
Mass (Weight)	lbs (kg)	48 (22)	